


REV.	ECN NUMBER	DESCRIPTION	DATE	DRAWN	CHECKED	APPROVED
X1	ECN23*	FIRST REASE	04/17' 23	梁兑泉	丁第斌	牛宝星



备注:

1. 材质: 塑胶壳: TPU, 黑色. SMA连接器, 镀镍.
2. 天线频率范围: 136MHz-145MHz, VSWR≤4.0, 1575MHz, VSWR≤2.5.
测试要求: 全检VSWR测试, 网分测试.
3. 标有“▼”为QC重点检测尺寸.
4. 盐雾48H.
5. 有害物质须符合ECT《QE-Q-19-001环境有害物质管理基准》管控标准.

NOTE:

1. Material: Plastic shell, TPU, black. SMA connector,
2. The antenna frequency range: 136MHz-145MHz, VSWR≤4.0, 1575MHz, VSWR≤2.5.
Pattern test requirements: all inspection VSWR test, test network points.
3. Marked "▼" size detection for QC.
4. Salt fog 48 h.
5. HSF shall conform to the standard QE-Q-19-001 Environmental Hazardous Substances Management.

镭雕字符说明

AF605: VHF + GNSS XX

AF605: VHF + GNSS XX

PC绿色色环配件

镭雕字符

产品型号

产品生产年份后两位, 例: 2023生产的镭雕23.

AF605:VHF#

GNSS XX

字符字体: Tahoma, 字符高度: T=2.20mm, 字符朝向: 字体顶部与配件进胶口&倒角面平行.

b	配件	1	AF605-胶杆天线, 直径14.0*2.5mm_PC绿色色环配件
a	半成品2	1	605_136-145MHz-胶杆, 带件注塑TPU, 黑色, 直径14*150.8
ITEM	PART NAME	Q' TY	MATERIAL / FINISH

	GENERAL TOLERANCE		SCALE: 1:1	DRAWN: 梁兑泉	DATE: 04/17' 23	DWG. NO: 600-V366-01	TITLE: ANT_EX_VHF+GNSS_TPU+shell-PH6_VHF-AF605	REV. X1
	.X±0.30	X.°±1°	UNIT: mm	CHECK:	DATE:	PARTS NO. (INTENDED USE): 81800V366	SHEET: 1/1	
	.XX±0.10	XX.°±1°	SIZE: A4	APPROVE:	DATE:			